<u>In the claims</u>:

Please substitute the following full listing of claim for the claims as originally filed or most recently amended.

1. (Currently amended)   A mobile communication terminal, wherein a battery is used as a power source, comprising:

a detector for detecting the voltage of the battery acting as a power source;

decision means for deciding a difference relationship between a voltage level detected by the detector and a prescribed value;

a transmission reservation controller <u>at said mobile communication terminal</u> for storing transmission data as transmission-reserved data into a storage <u>at said mobile communication terminal</u>, without starting the transmission operation, when the decision means decides that the detected voltage level is less than the prescribed value, in response to a data transmission request, and thus maintaining its wait state; and

a reserved-data transmission controller for radio-transmitting the transmission-reserved data ~~to be~~ stored in the storage <u>at said mobile communication terminal</u> when the decision means decides that the detected voltage level exceeds said prescribed value after maintenance of the wait state.

2. (Original)   The mobile communication terminal defined in Claim 1, wherein the transmission data comprises electronic mail data created in the wait state.

3. (Original)   The mobile communication terminal defined in Claim 2, further comprising an electronic mail data storage for temporarily storing the created

electronic mail data in the storage to wait decision
results by the decision means in advance of
transmission.

4. (Currently amended)   A mobile communication
terminal, wherein a battery is used as a power source,
comprising:

        a detector for detecting the voltage of the
battery acting as a power source;

        decision means for deciding a difference
relationship between a voltage level detected by the
detector and a prescribed value;

        a transmission reservation controller <u>at said
mobile communication terminal</u> for ceasing the
transmission operation, when the decision means decides
that the detected voltage level is less than the
prescribed value, during radio transmission of
transmission data, storing the transmission data as
transmission-reserved data into a storage <u>at said
mobile communication terminal</u>, and then changing the
mobile communication terminal to a wait state; and

        a re-transmission controller for radio-
transmitting again the transmission-reserved data ~~to be~~
stored in the storage when the decision means decides
that the detected voltage level exceeds the prescribed
value after a change to the wait state.

5. (Original)   The mobile communication terminal
defined in Claim 4, wherein the transmission data
comprises electronic mail data created in the wait
state.

6. (Original)   The mobile communication terminal
defined in Claim 5, further comprising an electronic
mail data storage for temporarily storing the created
electronic mail data in said storage to wait decision
results by the decision means in advance of
transmission.

7. (Currently amended)   A data transmission method
suitable for a mobile communication terminal which uses
a battery as a power source, comprising the steps of:
    detecting the voltage of the battery acting as a
power source;
    deciding a difference relationship between a
voltage level detected in the detecting step and a
prescribed value;
    storing transmission data as transmission-reserved
data to a storage <u>at said mobile communication
terminal</u>, without starting the transmission operation,
when it is decided <u>at said mobile communication
terminal</u> in the deciding step that the detected voltage
level is less than the prescribed value, in response to
a data transmission request, and then maintaining its
wait state; and
    radio-transmitting the transmission-reserved data
~~to be~~ stored in the storage when it is decided in the
deciding step that the detected voltage level exceeds
the prescribed value after maintenance of the wait
state.

8. (Original)   The data transmission method defined in
Claim 7, further comprising the step of charging said
battery after maintenance of the wait state.

9. (Original)   The data transmission method defined in
Claim 7, further comprising the step of replacing said
battery for a new one after maintenance of the wait
state.

10. (Original) The data transmission method defined in claim 7, further comprising the step of creating electronic mail data as said transmission data in the wait state.

11. (Original) The data transmission method defined in Claim 10, further comprising the step of temporarily storing said created electronic mail data into the storage to wait decision results in the deciding step in advance of transmission.

α3

12. (Currently amended) A data transmission method suitable for a mobile communication terminal which uses a battery acting as a power source, comprising the steps of:

    detecting the voltage of the battery acting as a power source; deciding a difference relationship between a voltage level detected by the detector and a prescribed value;

    ceasing the transmission operation when it is decided <u>at said mobile communication terminal</u> in the detecting step that the detected voltage level is less than the prescribed value, during radio transmission of transmission data, storing the transmission data as transmission-reserved data into a storage <u>at said mobile communication terminal</u>, and thus changing the mobile communication terminal to a wait state; and

    radio-transmitting again the transmission-reserved data ~~to be~~ stored in the storage when it is decided in the deciding step that the detected voltage level exceeds the prescribed value after a change to the wait state.

13. (Original) The data transmission method defined in Claim 12, further comprising the step of charging said battery after a change to said wait state.

14. (Original) The data transmission method defined in Claim 12, further comprising the step of replacing said battery for a new one after a change to said wait state.

15. (Original) The data transmission method defined in Claims 12, further comprising the step of creating electronic mail data as said transmission data in the wait state.

16. (Original) The data transmission method defined in Claim 15, further comprising the step of temporarily storing said created electronic mail data into the storage to wait decision results in the deciding step in advance of transmission.